

Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code:
Product name **BLACK WOOD PROTECTOR 300ML**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **FURNITURE OIL**

1.3. Details of the supplier of the safety data sheet

Name **Fenice S.p.A.**
Full address **Via del Lavoro, 1**
District and Country **36078 Valdagno (VI)**
Italia
tel. **+39.0445.424.888**

e-mail address of the competent person
responsible for the Safety Data Sheet **ufficio.sicurezza@fenice.com**

1.4. Emergency telephone number

For urgent inquiries refer to **FENICE S.p.A. Unip. - Tel. +39.0445.424.888 (8:00-12:00; 14:00-17:30)**

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Hazardous to the aquatic environment, chronic toxicity, category 3 **H412** Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: --

Signal words: --

Hazard statements:

H412 Harmful to aquatic life with long lasting effects.
EUH208 Contains: Mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one and 2-methyl-2h-isothiazol-3-one
methyl- 2H- isothiazol- 3-one (3:1)
1,2-Benzisothiazol-3(2H)-one
3- Iodo- 2-propynyl- N- butylcarbamate
May produce an allergic reaction.

Precautionary statements:

P273 Avoid release to the environment.

VOC (Directive 2004/42/EC) :

One - pack performance coatings.

VOC given in g/litre of product in a ready-to-use condition :

14,69

Limit value:

140,00

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration $\geq$ 0.1%.

BLACK WOOD PROTECTOR 300ML

Revision nr.12
Dated 07/04/2022
Printed on 21/04/2023
Page n. 2 / 20
Replaced revision:11 (Dated 05/04/2022)

EN

SECTION 3. Composition/information on ingredients ... / >>

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
3- Iodo- 2-propynyl- N- butylcarbamate		
CAS	55406-53-6	0,5 ≤ x < 1
EC	259-627-5	Acute Tox. 3 H331, Acute Tox. 4 H302, STOT RE 1 H372, Eye Dam. 1 H318, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=10, Aquatic Chronic 1 H410 M=1
INDEX	616-212-00-7	LD50 Oral: 1056 mg/kg, LC50 Inhalation mists/powders: 0,67 mg/l/4h
REACH Reg.		
2-BUTOXYETHANOL		
CAS	111-76-2	0,5 ≤ x < 1
EC	203-905-0	Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Eye Irrit. 2 H319, Skin Irrit. 2 H315
INDEX	603-014-00-0	LD50 Oral: 1414 mg/kg, LD50 Dermal: 1100 mg/kg, LC50 Inhalation vapours: 11 mg/l/4h
REACH Reg. 01-2119475108-36-xxxx		
TRIETHYLAMINE		
CAS	121-44-8	0,25 ≤ x < 0,5
EC	204-469-4	Flam. Liq. 2 H225, Acute Tox. 3 H311, Acute Tox. 3 H331, Acute Tox. 4 H302, Skin Corr. 1A H314, Eye Dam. 1 H318, STOT SE 3 H335
INDEX	612-004-00-5	STOT SE 3 H335: ≥ 1%
REACH Reg. 01-2119475467-26-xxxx		
1,2-Benzisothiazol-3(2H)-one		
CAS	2634-33-5	0 ≤ x < 0,05
EC	220-120-9	Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 2 H411
INDEX	613-088-00-6	Skin Sens. 1 H317: ≥ 0,05%
REACH Reg. 01-2120761540-60		
Mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one and 2-methyl-2h-isothiazol-3-one		
methyl- 2H- isothiazol- 3-one (3:1)		
CAS	55965-84-9	0 ≤ x < 0,0015
EC	911-418-6	Acute Tox. 2 H310, Acute Tox. 2 H330, Acute Tox. 3 H301, Skin Corr. 1B H314, Eye Dam. 1 H318, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=100, Aquatic Chronic 1 H410 M=100
INDEX	613-167-00-5	Skin Corr. 1B H314: ≥ 0,5%, Skin Corr. 1C H314: ≥ 0,6%, Skin Irrit. 2 H315: ≥ 0,06%, Skin Sens. 1A H317: ≥ 0,0015%, Eye Dam. 1 H318: ≥ 0,6%, Eye Irrit. 2 H319: ≥ 0,06%
REACH Reg. 01-2120764691-48-xxxx		
1-HYDROXYPYRIDINE-2-THIONE ZINC		
CAS	13463-41-7	0 ≤ x < 0,01
EC	236-671-3	LD50 Oral: >64 mg/kg, LD50 Dermal: >87 mg/kg, LC50 Inhalation mists/powders: 0,31 mg/l/4h
INDEX		
REACH Reg.		
ETHYL ACETATE		
CAS	141-78-6	0 ≤ x < 0,01
EC	205-500-4	Repr. 1B H360D, Acute Tox. 2 H330, Acute Tox. 3 H301, STOT RE 1 H372, Eye Dam. 1 H318, Aquatic Acute 1 H400 M=1000, Aquatic Chronic 1 H410 M=10
INDEX	607-022-00-5	LD50 Oral: 221 mg/kg, LC50 Inhalation mists/powders: 0,14 mg/l/4h
REACH Reg. 01-2119475103-46-XXXX		
CYCLOHEXANE		
CAS	110-82-7	0 ≤ x < 0,01
EC	203-806-2	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
INDEX	601-017-00-1	
REACH Reg.		
CYCLOHEXANE		
CAS	110-82-7	0 ≤ x < 0,01
EC	203-806-2	Flam. Liq. 2 H225, Asp. Tox. 1 H304, Skin Irrit. 2 H315, STOT SE 3 H336, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1
INDEX	601-017-00-1	
REACH Reg.		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage**7.1. Precautions for safe handling**

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection**8.1. Control parameters**

Regulatory References:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
CZE	Česká Republika	Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
EST	Eesti	Ohtlike kemikaalide ja neid sisaldavate materjalide kasutamise töötervishoiu ja tööohutuse nõuded ning töökeskonna keemiliste ohutegurite piirnormid [RT I, 17.10.2019, 1 - jõust. 17.01.2020]
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
FIN	Suomi	HTP-VÄRDEN 2020. Koncentrationer som befunnits skadliga. SOCIAL - OCH HÄLSOVÄRDSMINISTERIETS PUBLIKATIONER 2020:25
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α' 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία"»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelethez a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
LTU	Lietuva	Jsakymas dėl lietuvių higienos normos hn 23:2011 „cheminių medžiagų profesinio poveikio ribiniai dydžiai. Matavimo ir poveikio vertinimo bendrieji reikalavimai“ patvirtinimo
LVA	Latvija	Grozījumi Ministru kabineta 2007. gada 15. maija noteikumos Nr. 325 "Darba aizsardzības prasības saskarē ar ķīmiskajām vielām darba vietās" (prot. Nr. 32 18. §; prot. Nr. 1 22. §)
NOR	Norge	Forskrift om endring i forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og grenseverdier), 21. august 2018 nr. 1255
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru

BLACK WOOD PROTECTOR 300ML

Revision nr.12
Dated 07/04/2022
Printed on 21/04/2023
Page n. 5 / 20
Replaced revision:11 (Dated 05/04/2022)

EN

SECTION 8. Exposure controls/personal protection ... / >>

SVK	Slovensko	modificarea și completarea hotărârii guvernului nr. 1.093/2006 NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym a mutagénym faktorom pri práci v znení neskorších predpisov
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)
TUR	Türkiye	Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2021

AMORPHOUS SILICATE HYDRATE

Threshold Limit Value

Type	Country	TWA/8h mg/m3	ppm	STEL/15min mg/m3	ppm	Remarks / Observations
AGW	DEU	4				INHAL
MAK	DEU	4				INHAL
TLV	EST	2				
RV	LVA	1				
MV	SVN	4				INHAL

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
Inhalation	local	systemic	local	systemic	local	systemic	local	systemic
					4			4
					mg/m3			mg/m3

BLACK WOOD PROTECTOR 300ML

Revision nr.12
Dated 07/04/2022
Printed on 21/04/2023
Page n. 6 / 20
Replaced revision:11 (Dated 05/04/2022)

EN

SECTION 8. Exposure controls/personal protection ... / >>

CYCLOHEXANE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	700	200			
TLV	CZE	700	200,2	2000	572	
AGW	DEU	700	200	2800	800	
MAK	DEU	700	200	2800	800	
VLA	ESP	700	200			
TLV	EST	700	200			
VLEP	FRA	700	200	1300	375	11
HTP	FIN	350	100	875	250	
TLV	GRC	700	200			
AK	HUN	700				
GVI/KGVI	HRV	700	200			SKIN
VLEP	ITA	350	100			
RD	LTU	700	200			
RV	LVA	80	23			
TLV	NOR	525	150			
TGG	NLD	700		1400		
VLE	PRT	700	200			
NDS/NDSch	POL	300		1000		SKIN
TLV	ROU	700	200			
NPEL	SVK	700	200			
MV	SVN	700	200	2800	800	
ESD	TUR	700	200			
WEL	GBR	350	100	1050	300	
OEL	EU	700	200			
TLV-ACGIH		344	100			

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,207	mg/l
Normal value in marine water	0,207	mg/l
Normal value for marine water sediment	16,68	mg/kg
Normal value for the terrestrial compartment	3,38	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers		Chronic local	Chronic systemic	Effects on workers			
	Acute local	Acute systemic			Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				59,4 mg/kg bw/d				
Inhalation	412 mg/m3	412 mg/m3	206 mg/m3	206 mg/m3	1400 mg/m3	1400 mg/m3	700 mg/m3	700 mg/m3
Skin				1186 mg/kg bw/d				2016 mg/kg bw/d

BLACK WOOD PROTECTOR 300ML

Revision nr.12
Dated 07/04/2022
Printed on 21/04/2023
Page n. 7 / 20
Replaced revision:11 (Dated 05/04/2022)

EN

SECTION 8. Exposure controls/personal protection ... / >>

2-BUTOXYETHANOL

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	98	20	246	50	SKIN
TLV	CZE	100	20,4	200	40,8	SKIN
AGW	DEU	49	10	98 (C)	20 (C)	SKIN
MAK	DEU	49	10	98	20	SKIN Hinweis
VLA	ESP	98	20	245	50	SKIN
TLV	EST	98	20	246	50	
VLEP	FRA	49	10	246	50	SKIN
HTP	FIN	98	20	250	50	SKIN
TLV	GRC	120	25			
AK	HUN	98		246		SKIN
GVI/KGVI	HRV	98	20	246	50	SKIN
VLEP	ITA	98	20	246	50	SKIN
RD	LTU	50	10	100	20	SKIN
RV	LVA	98	20	246	50	SKIN
TLV	NOR	50	10			SKIN
TGG	NLD	100		246		SKIN
VLE	PRT	98	20	246	50	SKIN
NDS/NDSch	POL	98		200		SKIN
TLV	ROU	98	20	246	50	SKIN
NPEL	SVK	98	20	246	50	SKIN
MV	SVN	98	20	246	50	SKIN
ESD	TUR	98	20	246	50	SKIN
WEL	GBR	123	25	246	50	SKIN
OEL	EU	98	20	246	50	SKIN
TLV-ACGIH		97	20			

Predicted no-effect concentration - PNEC

Normal value in fresh water	8,8	mg/l
Normal value in marine water	0,88	mg/l
Normal value for fresh water sediment	34,6	mg/kg
Normal value for marine water sediment	3,46	mg/kg
Normal value for water, intermittent release	9,1	mg/l
Normal value of STP microorganisms	463	mg/l
Normal value for the food chain (secondary poisoning)	20	mg/kg
Normal value for the terrestrial compartment	3,13	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral	VND	26,7 mg/kg bw/d	VND	6,3 mg/kg bw/d				
Inhalation	147 mg/m3	426 mg/m3	147 mg/m3	59 mg/m3	246 mg/m3	663 mg/m3	VND	98 mg/m3
Skin	VND	89 mg/kg/d	VND	75 mg/kg/d	VND	89 mg/kg/d	VND	125 mg/kg/d

BLACK WOOD PROTECTOR 300ML

Revision nr.12
Dated 07/04/2022
Printed on 21/04/2023
Page n. 8 / 20
Replaced revision:11 (Dated 05/04/2022)

EN

SECTION 8. Exposure controls/personal protection ... / >>

ETHYL ACETATE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	734	200	1468	400	
TLV	CZE	700	191,1	900	245,7	
AGW	DEU	730	200	1460	400	
MAK	DEU	750	200	1500	400	
VLA	ESP	734	200	1468	400	
TLV	EST	500	150	1100	300	
VLEP	FRA	734	200	1468	400	
HTP	FIN	730	200	1470	400	
TLV	GRC	734	200	1468	400	
AK	HUN	734		1468		
GVI/KGVI	HRV	734	200	1468	400	
VLEP	ITA	734	200	1468	400	
RD	LTU	500	150	1100 (C)	300 (C)	
RV	LVA	200	54	1468	400	
TLV	NOR	734	200			
TGG	NLD	734		1468		
VLE	PRT	734	200	1468	400	
NDS/NDSch	POL	734		1468		
TLV	ROU	734	200	1468	400	
NPEL	SVK	734	200	1468	400	
MV	SVN	734	200	1468	400	
WEL	GBR	734	200	1468	400	
OEL	EU	734	200	1468	400	
TLV-ACGIH		1441	400			

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,26	mg/l
Normal value in marine water	0,026	mg/l
Normal value for fresh water sediment	1,25	mg/kg
Normal value for marine water sediment	0,125	mg/kg
Normal value for water, intermittent release	1,65	mg/l
Normal value of STP microorganisms	650	mg/l
Normal value for the food chain (secondary poisoning)	200	mg/kg
Normal value for the terrestrial compartment	0,24	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				4,5 mg/kg bw/d				
Inhalation	734 mg/m3	734 mg/m3	367 mg/m3	367 mg/m3	1468 mg/m3	1468 mg/m3	734 mg/m3	734 mg/m3
Skin				37 mg/kg bw/d			37 mg/kg bw/d	63 mg/kg bw/d

BLACK WOOD PROTECTOR 300ML

Revision nr.12
Dated 07/04/2022
Printed on 21/04/2023
Page n. 9 / 20
Replaced revision:11 (Dated 05/04/2022)

EN

SECTION 8. Exposure controls/personal protection ... / >>

TRIETHYLAMINE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	8,4	2	12,6	3	SKIN
TLV	CZE	8	1,904	12	2,856	SKIN
AGW	DEU	4,2	1	8,4 (C)	2 (C)	SKIN
MAK	DEU	4,2	1	8,4	2	
VLA	ESP	8,4	2	12,6	3	SKIN
TLV	EST	8,4	2	12,6	3	SKIN
VLEP	FRA	4,2	1	12,6	3	SKIN
HTP	FIN			4,2	1	SKIN
TLV	GRC	40	10	60	15	
AK	HUN	8,4		12,6		SKIN
GVI/KGVI	HRV	8,4	2	12,6	3	SKIN
VLEP	ITA	8,4	2	12,6	3	SKIN
RD	LTU	8,4	2	12,6	3	SKIN
RV	LVA	8,4	2	12,6	3	
TLV	NOR	8	2			SKIN
TGG	NLD	4,2		12,6		SKIN
VLE	PRT	8,4	2	12,6	3	SKIN
NDS/NDSch	POL	3		9		SKIN
TLV	ROU	8,4	2	12,6	3	SKIN
NPEL	SVK	8,4	2	12,6	3	SKIN
MV	SVN	8,4	2	12,6	3	SKIN
ESD	TUR	8,4	2	12,6	3	SKIN
WEL	GBR	8	2	17	4	SKIN
OEL	EU	8,4	2	12,6	3	SKIN
TLV-ACGIH			0,5		1	SKIN

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,11	mg/l
Normal value in marine water	0,011	mg/l
Normal value for fresh water sediment	1,575	mg/kg
Normal value for marine water sediment	0,158	mg/kg
Normal value for water, intermittent release	0,08	mg/l
Normal value of STP microorganisms	100	mg/l
Normal value for the terrestrial compartment	0,25	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers		Chronic local	Chronic systemic	Effects on workers			
	Acute local	Acute systemic			Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation					12,6 mg/m3	12,6 mg/m3	8,4 mg/m3	8,4 mg/m3
Skin								12,1 mg/kg/d

1,2-Benzisothiazol-3(2H)-one

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,00403	mg/l
Normal value in marine water	0,00040	mg/l
	3	
Normal value for fresh water sediment	0,0499	mg/kg/d
Normal value for marine water sediment	0,00499	mg/kg/d
Normal value for water, intermittent release	0,00011	mg/l
Normal value of STP microorganisms	1,03	mg/l
Normal value for the terrestrial compartment	3	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers		Chronic local	Chronic systemic	Effects on workers			
	Acute local	Acute systemic			Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation				1,2 mg/m3				6,81 mg/m3
Skin				0,345 mg/kg bw/d				0,966 mg/kg bw/d

BLACK WOOD PROTECTOR 300ML

Revision nr.12
Dated 07/04/2022
Printed on 21/04/2023
Page n. 10 / 20
Replaced revision:11 (Dated 05/04/2022)

EN

SECTION 8. Exposure controls/personal protection ... / >>

Mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one and 2-methyl-2h-isothiazol-3-one methyl- 2H- isothiazol- 3-one (3:1)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
AGW	DEU	0,2					
MV	SVN	0,05					

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,00339	mg/l
Normal value in marine water	0,00339	mg/l
Normal value for fresh water sediment	0,027	mg/kg
Normal value for marine water sediment	0,027	mg/kg
Normal value for water, intermittent release	0,00339	mg/l
Normal value of STP microorganisms	0,23	mg/l
Normal value for the terrestrial compartment	0,01	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		0,11 mg/kg bw/d		0,09 mg/kg bw/d				
Inhalation	0,02 mg/m3		0,04 mg/m3		0,04 mg/m3		0,02 mg/m3	

3- Iodo- 2-propynyl- N- butylcarbamate

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
MAK	DEU	0,005	0,058	0,116	0,01		

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,001	mg/l
Normal value in marine water	0,0001	mg/l
Normal value for fresh water sediment	0,017	mg/kg
Normal value for marine water sediment	0,002	mg/kg
Normal value of STP microorganisms	0,44	mg/l
Normal value for the food chain (secondary poisoning)	NEA	
Normal value for the terrestrial compartment	0,005	mg/kg
Normal value for the atmosphere	NPI	

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral	NPI	NPI	NPI	NPI				
Inhalation	NPI	NPI	NPI	NPI	1,16 mg/m3	0,07 mg/m3	1,16 mg/m3	0,23 mg/m3
Skin					NPI	NPI	NPI	2 mg/kg bw/d

1-HYDROXYPYRIDINE-2-THIONE ZINC

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,00009	mg/l
Normal value in marine water	0,00009	mg/l
Normal value for fresh water sediment	0,009	mg/kg
Normal value for marine water sediment	0,009	mg/kg
Normal value of STP microorganisms	0,01	mg/l
Normal value for the terrestrial compartment	1,02	mg/kg

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.
VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

SECTION 8. Exposure controls/personal protection ... / >>

Take the normal precautions for handling chemicals and apply an adequate standard of workplace hygiene.

Users must assess the risks in their workplace and adopt:

- Primary collective protective measures such as adequate natural ventilation and local extraction
- Personal protective equipment to manage the combination of residual risks

Personal protective equipment varies according to the possible exposure and hazardousness of the working conditions, so the final choice depends on the risk assessment.

HAND PROTECTION

Use category III chemical resistant gloves according to the EN 374 standard

Brief contact (splash protection) – non-exhaustive list

Suitable material: NITRILE RUBBER (NBR)

Glove thickness: greater than 0.4 mm

Breakthrough time: from 30 to 60 minutes

Breakthrough index: at least 2

The gloves must be replaced if there are signs of deterioration. In any case, users must assess the risks to determine the most suitable type of glove for the conditions of use.

SKIN PROTECTION

Wear work clothes and safety footwear that complies with EN ISO 20344

EYE PROTECTION

Wear safety glasses (EN 166).

RESPIRATORY PROTECTION

Use a mask with EN140 and/or EN136 approval, with an ABEK type filter (EN 14387)

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

NOTE: Determination of the flash point may be NA (not applicable), the product being non flammable.

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	viscous liquid	
Colour	milky	
Odour	characteristic	
Melting point / freezing point	not available	
Initial boiling point	> 65 °C	
Flammability	not applicable	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	not applicable	
Auto-ignition temperature	not available	
pH	7-9	
Kinematic viscosity	not available	
Solubility	soluble in water	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	1,04	
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

SECTION 9. Physical and chemical properties ... / >>

9.2.2. Other safety characteristics

Total solids (250°C / 482°F)	26,70 %		
VOC (Directive 2004/42/EC) :	1,41 % - 14,69	g/litre	
Explosive properties	not applicable		
Oxidising properties	not applicable		

SECTION 10. Stability and reactivity

1-HYDROXYPYRIDINE-2-THIONE ZINC

1-HYDROXYPYRIDINE-2-THIONE ZINC - Keep away from light. Incompatible materials: oxidising agents, heavy metals and reducing agents.

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

2-BUTOXYETHANOL

Decomposes under the effect of heat.

ETHYL ACETATE

May react with: acids,bases,strong oxidants.Attacks: aluminium.

Decomposes slowly into acetic acid and ethanol under the effect of light, air and water.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

CYCLOHEXANE

May react violently with: strong oxidants,liquid nitric oxide.Forms explosive mixtures with: air.

2-BUTOXYETHANOL

May react dangerously with: aluminium,oxidising agents.Forms peroxides with: air.

ETHYL ACETATE

Risk of explosion on contact with: alkaline metals,hydrides,oleum.May react violently with: fluorine,strong oxidising agents,chlorosulphuric acid,potassium tert-butoxide.Forms explosive mixtures with: air.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

2-BUTOXYETHANOL

Avoid exposure to: sources of heat,naked flames.

ETHYL ACETATE

Avoid exposure to: light,sources of heat,naked flames.

10.5. Incompatible materials

CYCLOHEXANE

Incompatible materials: natural rubbers,neoprene,polyvinyl chloride,polyethylene.

2-BUTOXYETHANOL

Incompatible with: oxidising substances,alkaline substances,light metals.

ETHYL ACETATE

Incompatible with: acids,bases,strong oxidants,aluminium,nitrates,chlorosulphuric acid.Incompatible materials: plastic materials.

10.6. Hazardous decomposition products

2-BUTOXYETHANOL

May develop: hydrogen.

ETHYL ACETATE

When heated to decomposition releases: harsh fumes,irritating vapours.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

SECTION 11. Toxicological information ... / >>

Information not available

Information on likely routes of exposure

CYCLOHEXANE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

CYCLOHEXANE

Irritating for the skin and mucous membranes, and may be absorbed by the skin; nerve damage can occur at high doses and is largely due to the cyclohexanone, its metabolite.

Interactive effects

CYCLOHEXANE

The substance may enhance the effects of agents such as tri-ortho-cresyl phosphate (TOCP).

ACUTE TOXICITY

ATE (Inhalation - mists / powders) of the mixture:	> 5 mg/l
ATE (Inhalation - vapours) of the mixture:	> 20 mg/l
ATE (Inhalation - gas) of the mixture:	0,0 mg/l
ATE (Oral) of the mixture:	Not classified (no significant component)
ATE (Dermal) of the mixture:	>2000 mg/kg

AMORPHOUS SILICATE HYDRATE

LD50 (Oral):	> 2000 mg/kg
LD50 (Dermal):	> 5000 mg/kg
LC50 (Inhalation mists/powders):	> 5 mg/l/4h

CYCLOHEXANE

LD50 (Oral):	1270 mg/kg
LD50 (Dermal):	> 2000 mg/kg
LC50 (Inhalation vapours):	13,9 mg/l/4h

2-BUTOXYETHANOL

LD50 (Oral):	1414 mg/kg Guinea pig
LD50 (Dermal):	1100 mg/kg
LC50 (Inhalation vapours):	11 mg/l/4h Rat

ETHYL ACETATE

LD50 (Oral):	5620 mg/kg bw
LD50 (Dermal):	> 20000 mg/kg
LC50 (Inhalation vapours):	> 22,5 mg/l/6h

TRIETHYLAMINE

LD50 (Oral):	460 mg/kg
LD50 (Dermal):	570 mg/kg
LC50 (Inhalation vapours):	7,2 mg/l/4h

1,2-Benzisothiazol-3(2H)-one

LD50 (Oral):	597 mg/kg
LD50 (Dermal):	> 2000 mg/kg

Mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one and 2-methyl-2h-isothiazol-3-one methyl- 2H- isothiazol- 3-one (3:1)

LD50 (Oral):	> 64 mg/kg
LD50 (Dermal):	> 87 mg/kg
LC50 (Inhalation mists/powders):	0,31 mg/l/4h

3- Iodo- 2-propynyl- N- butylcarbamate

LD50 (Oral):	1056 mg/kg
LD50 (Dermal):	> 2000 mg/kg
LC50 (Inhalation mists/powders):	0,67 mg/l/4h

SECTION 11. Toxicological information ... / >>

1-HYDROXYPYRIDINE-2-THIONE ZINC

LD50 (Oral):	221 mg/kg
LD50 (Dermal):	> 2000 mg/kg
LC50 (Inhalation mists/powders):	0,14 mg/l/4h

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.

Contains:

Mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one and 2-methyl-2h-isothiazol-3-one
methyl- 2H- isothiazol- 3-one (3:1)
1,2-Benzisothiazol-3(2H)-one
3- Iodo- 2-propynyl- N- butylcarbamate

Respiratory sensitization

Information not available

Skin sensitization

Information not available

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

Adverse effects on sexual function and fertility

Information not available

Adverse effects on development of the offspring

Information not available

Effects on or via lactation

Information not available

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

Target organs

Information not available

Route of exposure

Information not available

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

SECTION 11. Toxicological information ... / >>

Target organs

Information not available

Route of exposure

Information not available

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity

AMORPHOUS SILICATE HYDRATE

LC50 - for Fish	> 10000 mg/l/96h Brachydanio rerio
EC50 - for Algae / Aquatic Plants	> 10000 mg/l/72h Scenedesmus subspicatus

CYCLOHEXANE

LC50 - for Fish	4,53 mg/l/96h Pimephales promelas
EC50 - for Crustacea	0,9 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	32,7 mg/l/72h Chlorella vulgaris
Chronic NOEC for Algae / Aquatic Plants	0,952 mg/l 72 h

2-BUTOXYETHANOL

LC50 - for Fish	1474 mg/l/96h Oncorhynchus mykiss
EC50 - for Crustacea	1550 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	911 mg/l/72h Pseudokirchneriella subcapitata
Chronic NOEC for Fish	> 100 mg/l Brachydanio rerio
Chronic NOEC for Crustacea	100 mg/l Daphnia magna
Chronic NOEC for Algae / Aquatic Plants	88 mg/l

ETHYL ACETATE

LC50 - for Fish	230 mg/l/96h Pimephales promelas
EC50 - for Crustacea	165 mg/l/48h Daphnia cucullata
EC50 - for Algae / Aquatic Plants	> 100 mg/l/72h
Chronic NOEC for Fish	< 9,65 mg/l Pimephales promelas
Chronic NOEC for Crustacea	2,4 mg/l Daphnia magna (21 d)

TRIETHYLAMINE

LC50 - for Fish	24 mg/l/96h
EC50 - for Crustacea	17 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	8 mg/l/72h Pseudokirchneriella subcapitata
Chronic NOEC for Fish	3,2 mg/l Oncorhynchus mykiss (60d)
Chronic NOEC for Crustacea	11 mg/l Daphnia magna (21d)

1,2-Benzisothiazol-3(2H)-one

LC50 - for Fish	2,18 mg/l/96h Onchorhynchus mykiss
EC50 - for Crustacea	2,94 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	0,15 mg/l/72h Pseudokirchneriella subcapitata
EC10 for Algae / Aquatic Plants	0,0403 mg/l/72h
Chronic NOEC for Fish	1,3 mg/l Onchorhynchus mykiss
Chronic NOEC for Crustacea	1,2 mg/l Daphnia magna
Chronic NOEC for Algae / Aquatic Plants	0,04 mg/l Pseudokirchneriella subcapitata

Mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one and 2-methyl-2h-isothiazol-3-one methyl- 2H- isothiazol- 3-one (3:1)

LC50 - for Fish	0,58 mg/l/96h Danio rerio
EC50 - for Crustacea	0,16 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	0,0379 mg/l/72h Pseudokirchneriella subcapitata - growth rate

BLACK WOOD PROTECTOR 300ML

Revision nr.12
Dated 07/04/2022
Printed on 21/04/2023
Page n. 16 / 20
Replaced revision:11 (Dated 05/04/2022)

EN

SECTION 12. Ecological information ... / >>

Chronic NOEC for Fish	0,098 mg/l Oncorhynchus mykiss (28 d)
Chronic NOEC for Crustacea	0,004 mg/l Daphnia magna (21 d)
Chronic NOEC for Algae / Aquatic Plants	0,032 mg/l Pseudokirchneriella subcapitata

3- Iodo- 2-propynyl- N- butylcarbamate	
LC50 - for Fish	0,067 mg/l/96h Oncorhynchus mykiss
EC50 - for Crustacea	0,16 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	0,022 mg/l/72h Scenedesmus subspicatus
Chronic NOEC for Fish	0,049 mg/l Rainbow trout
Chronic NOEC for Algae / Aquatic Plants	0,0046 mg/l/72 Scenedesmus subspicatus

1-HYDROXYPYRIDINE-2-THIONE ZINC	
LC50 - for Fish	0,0026 mg/l/96h Pimephales promelas
EC50 - for Crustacea	0,0083 mg/l/48h Daphnia magna
Chronic NOEC for Fish	0,00122 mg/l Pimephales promelas
Chronic NOEC for Crustacea	0,0027 mg/l

12.2. Persistence and degradability

AMORPHOUS SILICATE HYDRATE	
Solubility in water	0,1 - 100 mg/l
Degradability: information not available	

CYCLOHEXANE	
Solubility in water	0,1 - 100 mg/l
Rapidly degradable	

2-BUTOXYETHANOL	
Solubility in water	1000 - 10000 mg/l
Rapidly degradable	

ETHYL ACETATE	
Solubility in water	> 10000 mg/l
Rapidly degradable	70%

TRIETHYLAMINE	
Solubility in water	> 10000 mg/l
Rapidly degradable	80% (21d)

1,2-Benzisothiazol-3(2H)-one
Rapidly degradable

Mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one and 2-methyl-2h-isothiazol-3-one
methyl- 2H- isothiazol- 3-one (3:1)
NOT rapidly degradable

3- Iodo- 2-propynyl- N- butylcarbamate	
Rapidly degradable	> 80%

1-HYDROXYPYRIDINE-2-THIONE ZINC	
NOT rapidly degradable	

12.3. Bioaccumulative potential

AMORPHOUS SILICATE HYDRATE	
Partition coefficient: n-octanol/water	0,53

CYCLOHEXANE	
Partition coefficient: n-octanol/water	3,44

2-BUTOXYETHANOL	
Partition coefficient: n-octanol/water	0,81

ETHYL ACETATE	
Partition coefficient: n-octanol/water	0,68
BCF	30

SECTION 12. Ecological information ... / >>

TRIETHYLAMINE

Partition coefficient: n-octanol/water 1,45
BCF < 0,5

1,2-Benzisothiazol-3(2H)-one

Partition coefficient: n-octanol/water 1,3

Mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one and 2-methyl-2h-isothiazol-3-one methyl- 2H- isothiazol- 3-one (3:1)

Partition coefficient: n-octanol/water 0,75

3- Iodo- 2-propynyl- N- butylcarbamate

Partition coefficient: n-octanol/water 2,81

1-HYDROXYPYRIDINE-2-THIONE ZINC

Partition coefficient: n-octanol/water 0,9

12.4. Mobility in soil

CYCLOHEXANE

Partition coefficient: soil/water 2,89

2-BUTOXYETHANOL

Partition coefficient: soil/water 0,45

TRIETHYLAMINE

Partition coefficient: soil/water 2,57

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

For disposal or recovery in EU countries , use the relevant waste code (EWC code) identified in the European Waste Catalogue. The producer of the waste must assign the EWC code according to the sector and type of process. Disposal must be carried out by an authorised waste management company.

After the producer of the waste has assigned the EWC code, the contaminated packaging must be sent for recovery or disposal in compliance with the European waste management regulations. Disposal must be carried out by an authorised waste management company.

For waste disposal or recovery in countries outside the EU, comply with the national or local regulations in force. For disposal or recovery of contaminated packaging in countries outside the EU, comply with the national or local regulations in force.

Waste transportation may be subject to regulations on transportation of hazardous goods.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number or ID number

not applicable

BLACK WOOD PROTECTOR 300ML

Revision nr.12
Dated 07/04/2022
Printed on 21/04/2023
Page n. 18 / 20
Replaced revision:11 (Dated 05/04/2022)

EN

SECTION 14. Transport information ... / >>

14.2. UN proper shipping name

not applicable

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

not applicable

14.6. Special precautions for user

not applicable

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

Only for uses exempt from EU DIRECTIVE 2004/42/CE.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage $\geq$ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

VOC (Directive 2004/42/EC) :

One - pack performance coatings.

SECTION 15. Regulatory information ... / >>

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Repr. 1B	Reproductive toxicity, category 1B
Acute Tox. 2	Acute toxicity, category 2
Acute Tox. 3	Acute toxicity, category 3
STOT RE 1	Specific target organ toxicity - repeated exposure, category 1
Asp. Tox. 1	Aspiration hazard, category 1
Skin Corr. 1A	Skin corrosion, category 1A
Eye Dam. 1	Serious eye damage, category 1
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Skin Sens. 1A	Skin sensitization, category 1A
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H225	Highly flammable liquid and vapour.
H360D	May damage the unborn child.
H310	Fatal in contact with skin.
H330	Fatal if inhaled.
H301	Toxic if swallowed.
H372	Causes damage to organs through prolonged or repeated exposure.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

SECTION 16. Other information ... / >>

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

02 / 03 / 12 / 14.